



FEATURES

- Identification methods include Face, Fingerprint/RFID and/or Password
- Elegant ergonomic design
- 4.3" TFT touch screen is user-friendly and very intuitive
- 6 user-defined function keys
- Contact relays for door access control (wires to door strike or 3rd party panel)
- Web server management software via IE browser
- Optional extendable scheduled-bell
- Infra-red optical system enables user identification in poorly lit environments
- Optional built-in battery backup provides approx 4 hours continuous operation
- Optional built-in wireless Wi-Fi or GPRS for wireless communication
- Built-in contacts for 3rd party electric lock, door sensor, alarm, exit button, or bell
- Wiegand Output for connections to 3rd party access control panels

SPECIFICATION

Display	4.3" TFT touch screen Face 1200 (1:N)
Face capacity	1200 (1:N)
Fingerprint capacity	2000
ID Card capacity	10,000
Logs capacity	100,000
Algorithm Version	ZK Face 7.0 & ZK Finger 10.0
2000mAh backup battery	Optional
Communication	TCP/IP, RS232/485
USB-HOST	Two USB-Host
Wireless Wi-Fi	Optional
Time attendance Standard functions	ID Card (202 Optional), Automatic Status Switch, Self-Service Query, Work Code, T9 input, 9 digit user ID, DLST
Access control interfaces for	3rd party electric lock, door sensor, exit button
Wiegand Signal	Output
Optional functions	Serial printer, Mifare card, Extendable Scheduled-bell, Short Message, Web-server, GPRS
Power supply	12VDC 3A
Verification Speed	≤ 2 sec
Operating temp	0 °C - 45 °C
Operating Humidity	20% - 80%
Dimension (W×H×D)	193.6×147.6×101 mm
Gross Weight	1.8 kg

